

Technical data sheet

Quick-Step Palazzo

Edition	06.2013	Norm	Parameters	Norm requirements	Quick-Step values
Dimensions					
Panel					1820x190 mm
overall thickness					14,0 mm
panels per pack					6
m ² per pack					2,0750 m ²
Panel construction					
Surface layer			PEFC, FSC or legally controlled sources		3,0 mm
Coreboard					Hevea QS Mastercore
Backing layer			PEFC, FSC or legally controlled sources	Spruce or Pine	2,00 mm
Tongue and groove			Lengthwise		Uniclic
			Width		Uniclic Multifit
Surface layer					
wood species				Oak	
origine				Europe	
finishing					crf catalogue/website
grading					crf catalogue/website
Installation					
floating			on Quick-Step underlay	cf installation instructions	
glued to subfloor			Quick-Step MS polymere resin	cf installation instructions	
CE		EN 14342:2008	notified body	DAP-PL-1033.00	level 4
PEFC					PEFC label
Warranty			Uniclic connection domestic use commercial use	warranty conditions in each pack	lifetime levenslang on request
Finishing		UV-curing varnish oil			5 to 7 layers 2 layers
Wear resistance		SIS 923509 DIN 68861	falling sand S33 anti-scratch Top Coat with nano-technology		500-1700 550-1200
Scratch resistance		EN 13442		all except blue ink blue ink	class 5 class 3
Stain resistance					
General aspect of installed flooring	EN 13489		lippings - difference in height difference in width cupping lengthwise cupping in width	≤ 0,20 mm ≤ 0,20 mm ≤ 0,1% ≤ 0,2 %	≤ 0,15 mm ≤ 0,15 mm ≤ 0,1 % ≤ 0,2 %
Castor chairs				use soft castors Type W (EN 12529) and/or suitable office mat	
Slip resistance	CEN/TS 15676				USRV 50-52
Formaldehyde emission	EN 717-1				E1
PCP					below detection limit
Heat resistance	EN 12664				0,127 m ² .°K/W
Underfloor heating				consult special installation instructions	
Reaction to fire	EN 14342	CWFT	With an oak toplayer		D _{fl} - s ₁ C _{fl} - s ₁

UNILIN Flooring bvba - Ooigemstraat 3 - 8710 Wielsbeke - België
E-mail: technical.service@quick-step.com Tel : +32 56 67 52 37 Fax : +32 56 67 52 39