

Technical data sheet

Quick-Step Villa

Edition	01.2013	Norm	Parameters	Norm requirements	Quick-Step values
Dimensions					
Panel					2200x190 mm
overall thickness					14,0 mm
panels per pack					6
m ² per pack					2,5080 m ²
Panel construction					
Surface layer			PEFC, FSC or legally controlled sources		3,0 mm
Coreboard				Spruce or Pine	Hevea QS Mastercore
Backing layer			PEFC, FSC or legally controlled sources		2,00 mm
Tongue and groove			Lengthwise		Uniclic
			Width		Uniclic Multifit
Surface layer					
wood species				Oak, walnut, merbau, Jatoba	steamed beech, Doussie
origine				Europe, USA, Malaysia, Brazil	Nigeria, Ghana
finishing					crf catalogue/website
grading					crf catalogue/website
Installation					
floating			on Quick-Step underlay	cf installation instructions	
glued to subfloor			Quick-Step MS polymere resin	cf installation instructions	
CE		EN 14342:2008	notified body	DAP-PL-1033.00	level 4
PEFC					PEFC label
Warranty			Uniclic connection domestic use commercial use	warranty conditions in each pack	lifetime lifetime on request
Finishing		UV-curing varnish			5 tot 7 lagen
Wear resistance		SIS 923509	falling sand		800-1000
Scratch resistance		DIN 68861	S33		100-1050
Stain resistance		EN 13442	anti-scratch Top Coat with nano-technology	all except blue ink blue ink	class 5 class 3
General aspect of installed flooring		EN 13489	lipping - difference in height difference in width cupping lengthwise cupping in width	≤ 0,20 mm ≤ 0,20 mm ≤ 0,1% ≤ 0,2 %	≤ 0,15 mm ≤ 0,15 mm ≤ 0,1 % ≤ 0,2 %
Castor chairs				use soft castors Type W (EN 12529) and/or suitable office mat	
Slip resistance		CEN/TS 15676			USRV 50-52
Formaldehyde emission		EN 717-1			E1
PCP					below detection limit
Heat resistance		EN 12664			0,127 m ² .°K/W
Underfloor heating				consult special installation instructions	
Reaction to fire		EN 14342	CWFT		D _{fl} - s ₁
			With an oak toplayer		C _{fl} - s ₁
UNILIN Flooring bvba - Ooigemstraat 3 - 8710 Wielsbeke - België E-mail: technical.service@quick-step.com Tel : +32 56 67 52 37 Fax : +32 56 67 52 39					