ECONOMICAL

You can use any spare pieces of profile for other purposes, you won't have any excess profiles or leftovers.





As an **expansion profile** to connect 2 floors of the same height.



As an **adapter profile** to connect a Quick Step® floor with another type of floor covering which is lower.



As an **end profile** next to e.g. a wall or a window.



As a **transition** to a carpet.



To finish off your stairs

Create stairs that fit perfectly into your interior with incizo®



Applicable to many staircases

Straight or turning. With or without stair nose. Flush or non flush installation.

Simple and fast

No annoying demolition work. Facelift your stairs in less than a

Seamless and subtle

There's an incizo® profile for each Quick-Step® floor, with a perfectly matching colour. The result is a discrete and seamless transition to your floor.

Solid as a rock

The combination of a strong aluminium sub-profile, Quick-Step® One4All Glue, screws and the Quick-Step® Incizo® profile composed of quality materials, results in a solid stair solution you can rely upon.

Scratch-resistant surface.

A variety in stair finishes with one and the same profile

A. Modern stairs with clean lines

More info on page 4



Use the included slitter to cut off a part of the Incizo® profile. The result is nice flat stair risers.

B. Stairs with stair noses



Finish both the treads and the stair risers with Quick Step® planks.
The result is a stylish eye-catcher that perks up your interior.



More info on page 5

Finishing stairs with painted stair risers is possible. Paint e.g. the stair riser in a colour which contrasts with the rest of your stairs, to accentuate your staircase.

Finishing stairs with stair noses is easy. Here again you can have the stair risers finished with Quick·Step® planks, or opt for paint.











Spacers not offered by Quick·Step®

C. A non-flush installation



There is also an Incizo® solution for this. Simply turn around the aluminium sub-profile, so the short leg is resting on the stair tread. Cut off a part of the Incizo® profile with the Incizo® slitter. Stick the Incizo® profile onto its sub-profile. Ready!*

* Non-flush installation is required e.g. when the Incizo® profile covers a transition to an existing floor.

Check out our installation video on www.quick-step.com

Ask your dealer for advice on the correct aluminium sub-profile for the Quick·Step® floor of your choice.

(sub-profile to be ordered separately)

Simple and fast installation

Modern stairs with clean lines.



Start at the top of the stairs and work downwards.



Glue and screw the aluminium sub-profile onto the step.



Glue the plank to the riser with Quick-Step One4All glue. The spacers ensure that sufficient space is left underneath to fit in the next step.



Apply glue to the sub-profile and the step. Spread the glue out across the sub-profile.



Place a plank on the step against the rising edge of the sub-profile. Push the plastic strip* on the tongue of the plank.



Cut off part A of the Incizo® with the Incizo® knife (see instructions included in Incizo® packaging). Apply glue to both sides of the Incizo® base.



Press the Incizo® profile onto its sub-profile and position it nicely for a level transition with the rest of the tread. Repeat the installation for the rest of the stairs.



Ask your dealer for advice on the correct aluminium sub-profile for the Quick·Step® floor of your choice. (sub-profile to be ordered separately)



Simple and fast installation Stairs with stair noses.

Start at the top of the stairs and work downwards.





Apply Quick*Step® One4All Glue to a panel Glue and screw the aluminium sub-profile to and put it against the stair riser. The panel the stairs. should come a bit lower than the stair tread. Put two spacers under the panel. This will enable you later to easily insert the tread plank under the stair riser plank.






Apply glue to the sub-profile and the rest of Place a plank on the step against the rising spread on the sub-profile.







Apply glue to both sides of the Incizo® base.







Ask your dealer for advice on the correct aluminium sub-profile for the floor of your choice. (sub-profile to be ordered separately)

^{*}Depending on the type of subprofile you bought, it is supplied with or without a plastic insert. If a plastic insert is included, the way of installing depends on the floor thickness, carry out as indicated in the technical datasheet. If insert not included: apply glue to the tongue of the plank.



